

2019

11503

19.1.0

ISO9001

ISO14001

OHSAS18001

/

.....	1
.....	1
.....	1
.....	2
.....	3
.....	5
.....	5
.....	6
.....	6
.....	6

1	YM-1			
2	YM-2			
3	YM-3			
4	YM-5			
5	YM-7			
6	XYM-1			
7	XYM-2			
8	XYM-3			
9	XYM-5			
10	XYM-7			

1	YM-1	-15 ~45	0.96-2.0g/cm ³ 8.0-171b/gal	0.01g/cm ³ (0.11b/gal)	140 mL
2	YM-2	-15 ~45	0.96-2.5g/cm ³ 8.0-211b/gal	0.01g/cm ³ (0.11b/gal)	140 mL
3	YM-3	-15 ~45	0.96-3.0g/cm ³ 8.0-251b/gal	0.01g/cm ³ (0.11b/gal)	140 mL

4	YM-5	-15 ~45	0.7-2.4g/cm ³ 5.8-201b/gal	0.01g/cm ³ (0.11b/gal)	140 mL
5	YM-7	-15 ~45	0.1-1.5g/cm ³ 0.8-131b/gal	0.01g/cm ³ (0.11b/gal)	140 mL
6	XYM-1	-15 ~45	0.96-2.0g/cm ³ 8.0-171b/gal	0.01g/cm ³ (0.11b/gal)	140 mL
7	XYM-2	-15 ~45	0.96-2.5g/cm ³ 8.0-211b/gal	0.01g/cm ³ (0.11b/gal)	140 mL
8	XYM-3	-15 ~45	0.96-3.0g/cm ³ 8.0-251b/gal	0.01g/cm ³ (0.11b/gal)	140 mL
9	XYM-5	-15 ~45	0.7-2.4g/cm ³ 5.8-201b/gal	0.01g/cm ³ (0.11b/gal)	140 mL
10	XYM-7	-15 ~45	0.1-1.5g/cm ³ 0.8-131b/gal	0.01g/cm ³ (0.11b/gal)	140 mL

1

2

3

4

5

1g/cm^3

21

/ (lb/gal.)	/ (lb/in)	/ (g/cm)	/ (kg/m)
6.5	48.6	0.78	780
7.0	52.4	0.84	840
7.5	56.1	0.90	900
8.0	59.8	0.96	960
8.3	62.3	1.00	1000
8.5	63.6	1.02	1020
9.0	67.3	1.08	1080
9.5	71.1	1.14	1140
10.0	74.8	1.20	1200
10.5	78.5	1.26	1260
11.0	82.3	1.32	1320
11.5	86.0	1.38	1380
12.0	89.8	1.44	1440
12.5	93.5	1.50	1500
13.0	97.2	1.56	1560
13.5	101.0	1.62	1620
14.0	104.7	1.68	1680
14.5	108.5	1.74	1740
15.0	112.5	1.80	1800
15.5	115.9	1.86	1860
16.0	119.7	1.92	1920
16.5	123.4	1.98	1980
17.0	127.2	2.04	2040
17.5	130.9	2.10	2100
18.0	134.6	2.16	2160
18.5	138.4	2.22	2220
19.0	142.1	2.28	2280
19.5	145.9	2.34	2340

20.0	149.6	2.40	2400
20.5	153.3	2.46	2460
21.0	157.1	2.52	2520
21.5	160.8	2.58	2580
22.0	164.6	2.64	2640
22.5	168.3	2.70	2700
23.0	172.1	2.76	2760
23.5	175.8	2.82	2820
24.0	179.5	2.88	2880

1

2

3

4

1

2

5

3

GB/T 25480-2010

1

2

3

320

10

0532-87605016/87605018

0532-87660287

0532-87604773

www.haitongda.com

haitongda@vip.sina.com